


444788

Ready

MATERIAL SAFETY DATA SHEET

OSHA - Meets 29 CFR 1910.1200 Standards	HMIS HAZARD RATINGS		
	HEALTH	2	0 = INSIGNIFICANT 3 = HIGH
	FLAMMABILITY	4	1 = SLIGHT 4 = EXTREME
	REACTIVITY	1	2 = MODERATE
TRANSPORTATION INFORMATION			
PROPER SHIPPING NAME:		Consumer Commodity	
HAZARD CLASS / PKG GRP:		ORM - D / None	REF: 49 CFR 173.306
IDENTIFICATION NUMBER:		None	LABEL: CONSUMER COMMODITY

SECTION 1 - PRODUCT / COMPANY IDENTIFICATION

IDENTITY (AS USED ON LABEL AND LIST) 70% VOC AIR FRESHENER (07901 through 07923)		Page 1 of 2
MANUFACTURER'S NAME Hospital Specialty Company	EMERGENCY TELEPHONE NUMBER CHEM - TEL (800) 255-9924 Outside USA (813) 248-0585	
ADDRESS (NUMBER, STREET, P.O. BOX) 670 Alpha Drive	TELEPHONE NUMBER FOR INFORMATION (440) 720-1800	
(CITY, STATE AND ZIP CODE) Highland Heights, OH 44143	DATE PREPARED: March 15, 2002 SUPERSEDES: December 15, 2001	

SECTION 2 - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

HAZARDOUS COMPONENTS (SPECIFIC CHEMICAL IDENTITY; COMMON NAME(S))	CAS #	% (OPTIONAL)	OSHA PEL		ACGIH TWA		SARA TITLE III	RQ LBS
			PPM	MG/M ³	PPM	MG/M ³		
Petroleum distillate, aliphatic	64742-47-8	15 - 40	100	525				
Ethanol	64-17-5	10 - 30	1000	1900	1000			
Propane	74-98-6	10 - 30	1000	1800	2500			
Isobutane	75-28-5	5 - 10	not established					
Butane	106-97-8	7 - 13	800	1900	800			

SECTION 3 - HEALTH HAZARD DATA

ROUTES OF ENTRY - SIGNS AND SYMPTOMS OF EXPOSURE	EMERGENCY AND FIRST AID PROCEDURES
INHALATION: High concentrations are irritating to the respiratory tract; may cause headache, dizziness, nausea, vomiting and malaise.	Remove affected person to fresh air; provide oxygen if breathing is difficult; if affected person is not breathing, administer CPR and seek emergency medical attention.
SKIN: Brief contact may cause slight irritation; prolonged contact may cause moderate irritation or dermatitis.	Remove contaminated clothing; wash affected area with soap and water; launder contaminated clothing before reuse; if irritation persists, seek medical attention.
EYES: High vapor concentration or contact may cause irritation and discomfort.	Remove contact lenses. Flush eyes with clear running water for 15 minutes while holding eyelids open; if irritation persists, seek medical attention.
INGESTION: May result in vomiting; aspiration of vomitus into the lungs must be avoided; DO NOT induce vomiting. Minute amounts aspirated into the lungs can produce severe lung injury, chemical pneumonitis, pulmonary edema or death.	DO NOT induce vomiting; if vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquid into lungs; seek immediate medical attention. Vomiting may be induced only under the supervision of a physician.

CARCINOGENICITY	NTP?	No	IARC MONOGRAPHS?	No	OSHA REGULATED?	No
-----------------	------	----	------------------	----	-----------------	----

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Preexisting skin, eye, or respiratory disorders may become aggravated through prolonged exposure.

Form revised 09 / 01

MATERIAL SAFETY DATA SHEET			
IDENTITY (AS USED ON LABEL AND LIST) 70% VOC AIR FRESHENER (07901 through 07918)		Page 2 of 2 Date: March 16, 2002	
SECTION 4 - FIRE FIGHTING MEASURES			
FLASH POINT (METHOD USED) -155° F (-104° C) TCC Propane)	NFPA RATING 2A	FLAMMABLE LIMITS LEL: 2.2% UEL: 9.5%	
EXTINGUISHING MEDIA Carbon dioxide, water fog, dry chemical, chemical foam			
SPECIAL FIRE FIGHTING PROCEDURES Firefighters must wear full facepiece self-contained breathing apparatus in positive pressure mode. Do not use solid stream of water since stream will scatter and spread fire. Fine water spray can be used to keep fire-exposed containers cool. Caution - material is flammable!			
UNUSUAL FIRE AND EXPLOSION HAZARDS Closed containers can explode due to buildup of pressure when exposed to extreme heat; do not use direct stream of water on pool fires as product may reignite on water surface. Contents under pressure. Do not use or store near heat or ignition source.			
SECTION 5 - ACCIDENTAL RELEASE MEASURES			
STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: CAUTION - EXTREMELY FLAMMABLE - EXTREMELY VOLATILE - Evacuate and ventilate area, remove all sources of ignition. Product will dissipate rapidly.			
SECTION 6 - HANDLING AND STORAGE			
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Keep container closed when not in use; protect containers from abuse; protect from extreme temperatures. CAUTION - EXTREMELY FLAMMABLE - keep away from all sources of ignition. "Empty" containers may contain residue which may form explosive vapors. Do not puncture container. Do not attempt to refill container. Maintain well ventilated work areas to minimize exposure when handling this material.			
SECTION 7 - EXPOSURE CONTROLS / PERSONAL PROTECTION			
RESPIRATORY PROTECTION (SPECIFY TYPE): None required while threshold limits (Section 2) are kept below maximum allowable concentrations; if TWA exceeds limits, NIOSH approved respirator must be worn. Refer to 29 CFR 1910.134 or European Standard EN 149 for complete regulations.			
VENTILATION LOCAL EXHAUST: Required MECHANICAL (GENERAL): Yes		SPECIAL: To maintain minimum TWA and STEL levels. OTHER: Engineering and work controls as required.	
PROTECTIVE GLOVES: Nitrile or rubber gloves with cuffs.		EYE PROTECTION: Protective eyeglasses or chemical safety goggles.	
OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Safety eyewash nearby			
WORK / HYGIENIC PRACTICES: Practice safe workplace habits. Minimize body contact with this, as well as all chemicals in general.			
SECTION 8 - PHYSICAL / CHEMICAL PROPERTIES			
BOILING POINT -44.5° F (-42.5° C)	SPECIFIC GRAVITY (WATER = 1) 0.790		
VAPOR PRESSURE (MM Hg) Not available	pH Not available		
VAPOR DENSITY (AIR = 1) > 1	EVAPORATION RATE (N-Butyl Acetate = 1) < 1		
SOLUBILITY IN WATER Partially soluble	% VOLATILE (BY WEIGHT) > 94%		
APPEARANCE AND ODOR Colorless liquid, various odors	VOLATILE ORGANIC COMPOUNDS (VOC's) 4.6 lbs / gallon		
SECTION 9 - STABILITY AND REACTIVITY			
STABILITY UNSTABLE: STABLE: XXX	CONDITIONS TO AVOID: Extreme temperatures, open flames, sparks		
INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizers, strong acids			
HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Decomposition will not occur if handled and stored properly. In case of a fire, oxides of carbon, hydrocarbons, fumes, and smoke may be produced.			
HAZARDOUS POLYMERIZATION MAY OCCUR: WILL NOT OCCUR: XXX	CONDITIONS TO AVOID: None		
SECTION 10 - DISPOSAL CONSIDERATIONS			
WASTE DISPOSAL METHOD: Dispose of in accordance with Local, State, and Federal Regulations. This product may produce concentrated hazardous vapors or fumes in a disposal container creating a dangerous environment. Refer to "40 CFR Protection of Environment Parts 260 - 299" for complete waste disposal regulations for ignitable materials. Consult your local, state, or Federal Environmental Protection Agency before disposing of any chemicals.			
The information contained herein is believed to be accurate but is not warranted to be so. Data and calculations are based on information furnished by the manufacturer of the product and manufacturers of the components of the product. Users are advised to confirm in advance of need that information is current, applicable and suited to the circumstances of use. Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, vendor assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety procedures are followed. Any questions regarding this product should be directed to the manufacturer of the product as described in Section 1.			