

SAVOGRAN COMPANY  
P.O. BOX 130, NORWOOD, MA 02062-0130  
(800) 225-9872

NFPA HAZARD CODE  
HEALTH-1 FIRE-1 REACTIVITY-0

### MATERIAL SAFETY DATA SHEET

TRADE NAME: SAVOGRAN DIRTEX Spray Cleaner (Aerosol)  
CHEMICAL NAME: Mixture C.A.S. No.: Not Applicable Class: CLEANING COMPOUND  
DOT SHIPPING NAME AND LABELING: Cleaning Compound - Consumer Commodity ORM-D

EFFECTIVE DATE: July, 1999

#### SECTION 2

#### HAZARDOUS INGREDIENTS

	C.A.S. No	Wt %	Exposure Guidelines
2-Butoxyethanol*	111-76-2	<8	OSHA 50 ppm TWA-Skin ACGIH 20 ppm TWA-Skin
Ammonia	7664-41-7	<2	OSHA 50 ppm TWA ACGIH 25 ppm TWA ACGIH 35 ppm STEL
Butane/Propane Mix:		<4	
Butane	106-97-8		ACGIH 800 ppm TWA
Propane	74-98-6		OSHA 1000 ppm TWA/ACGIH 2500 ppm TWA
Water	7732-18-51	Balance	

NOTE: Flammable contents less than 20% of total. Level 1 Aerosol  
SARA REQUIREMENTS: This product contains toxic chemicals (marked "\*" in SECTION 2)  
listed in paragraph 373.65 which are subject to reporting requirements of section 313  
of title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR  
Part 372.

#### SECTION 3

#### PHYSICAL DATA

Initial Boiling Point of product without propellant: 212°F	Specific Gravity: @ 60/60°F: 0.98
Vapor Pressure: Unknown	Percent Volatile: Essentially 100%
Vapor Density: Heavier than air	Evaporation Rate: Less than ether
Solubility in water: Total	Appearance: Clear, colorless liquid with mild, aromatic ammoniacal odor
VOC (% by wt.): 10	pH: 11 - 11.5

#### SECTION 4

#### FIRE AND EXPLOSION DATA

FLASH POINT: Flame extinguished by spray. (Consumer Product Safety Commission method 16 CFR 1500.45) Level 1 Aerosol  
FLASH POINT OF LIQUID: Above 135°F, (T.C.C.)

FLAMMABLE LIMITS: Unknown

EXTINGUISHING MEDIA: Alcohol foam, water fog, carbon dioxide or dry chemical

HAZARDOUS DECOMPOSITION PRODUCTS: May form toxic materials: carbon dioxide, carbon monoxide, various hydrocarbons, etc.

SPECIAL FIREFIGHTING PROCEDURES: Wear self-contained breathing apparatus with full face piece operated in pressure-demand or other positive pressure mode.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Contents under pressure. Do not puncture or incinerate container. Do not expose to heat or prolonged sunshine or store at temperature above 120°F, even when empty because container can explode.

#### SECTION 5

#### HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: See Section 2

EFFECTS OF EXPOSURE - Routes of Entry - Acute (immediate)

Eyes: Can cause severe irritation, redness, tearing, blurred vision.

Skin: Short contact - no irritation. Prolonged or frequently repeated contact can cause irritation, defatting, dermatitis.

Inhalation: Excessive inhalation of vapors can cause nasal and respiratory irritation, dizziness, weakness, fatigue, headache, nausea, possible unconsciousness and even asphyxiation.

Swallowing: Can cause gastrointestinal irritation, nausea, vomiting and diarrhea.

EFFECTS OF EXPOSURE - Chronic (delayed)

Carcinogenicity: NTP? No IARC MONOGRAPHS? No OSHA REGULATED? No

Eyes: No chronic effects expected.

Skin: No chronic effects expected.

Inhalation: When used as intended, no chronic effects expected.

Swallowing: If large amounts are ingested, organic injury to liver and kidneys may occur.

## MSDS Savogran DIRTEX Spray Cleaner (Aerosol)

## SECTION 5 HEALTH HAZARD DATA CONTINUED

FIRST AID:

Eyes: Flood with plenty of water with eye lids held open for at least 15 minutes and get medical attention promptly.

Skin: Wash thoroughly with soap and water. Thoroughly launder contaminated clothing before reuse.

Inhalation: If illness occurs, remove patient to fresh air. If breathing is difficult, give oxygen. If breathing has stopped, start artificial respiration. Call physician immediately.

Swallowing: Do not induce vomiting. Keep person warm and quiet and get medical attention. Aspiration of material into lungs due to vomiting can cause chemical pneumonitis which can be fatal.

## SECTION 6

## REACTIVITY DATA

STABILITY: Stable                    HAZARDOUS POLYMERIZATION: Will not occur.

INCOMPATIBILITY (materials to avoid): Strong oxidizing agents

CONDITIONS TO AVOID: See "SECTION 4 - UNUSUAL FIRE AND EXPLOSION HAZARDS."

## SECTION 7

## SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Review "SECTION 4 - UNUSUAL FIRE AND EXPLOSION HAZARDS."

SMALL SPILLS: Absorb liquid in paper, vermiculite, floor absorbent, or other absorbent material.

LARGE SPILLS: Same as small spill. Eliminate all ignition sources.

DISPOSAL OF WASTE: Contaminated absorbent must be disposed of in accordance with all local, state and federal regulations.

## SECTION 8

## SPECIAL PROTECTION INFORMATION

VENTILATION: Use local exhaust to control vapors

RESPIRATORY PROTECTION: If TLV of the product or any component is exceeded, a NIOSH/MSHA respirator is advised (See your safety equipment supplier.)

GLOVES: None required, when used as intended.

EYE PROTECTION: None required, when used as intended

OTHER PROTECTIVE EQUIPMENT: No special protective clothing needed.

## SECTION 9

## SPECIAL PRECAUTIONS

EMPTIED CONTAINERS: May retain product residues (e.g., vapor or liquid); therefore, all precautions given in this sheet must be observed.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Store in cool place, out of hot sun and below 100°F. Keep away from heat, sparks and open flames. Do not puncture or incinerate container even when empty because container may explode.